



tipo		TS-SP 500	TS-SP 800	TS-SP 1000	TS-SP 1500
Contenuto totale	litri	500	800	1000	1500
Press. mass. nel boiler	bar	3,0	3,0	3,0	3,0
Temp. mass.	°C	95	95	95	95
Press. mass. scambiatore	bar	10,0	10,0	10,0	10,0
Temp. mass. scambiatore	°C	110	110	110	110
Superficie scambiatore	m <sup>2</sup>	2,3	2,8	3,0	3,7
Altezza	mm	1720	1910	2090	2220
Diametro esterno	mm	850	990	990	1200
Diametro interno	mm	650	790	790	1000
Peso (senza isolamento)	kg	110	150	170	230
Raccordo No. 1	H mm 1 1/2"	1720	1910	2090	2220
Raccordo No. 2	A mm 1 1/2"	1400	1573	1742	1808
Raccordo No. 3	B mm 1 1/2"	1150	1390	1520	1635
Raccordo No. 4	C mm 1/2"	1 1/2" - 1020	1290	1450	1525
Raccordo No. 5	E mm 1 1/2"	910	980	1060	1085
Raccordo No. 6	F mm 1"	800	820	880	875
Raccordo No. 7	G mm 1 1/2"	650	670	730	765
Raccordo No. 8	L mm 1/2"	490	465	495	520
Raccordo No. 9	M mm 1"	280	310	310	375
Raccordo No. 10	N mm 1 1/2"	150	170	170	235
Raccordo No. 11 (Øest 180-Øint 110)	P mm	308	338	338	403
Raccordo No. 12	R mm 1/2"	440	570	580	875
Raccordo No. 13	S mm 1 1/2"	820	920	1130	1130
Raccordo No. 14	T mm 1/2"	1150	1290	1500	1500